

May 20th, 12:30 PM

A Reduced Order Model For Efficient Physiological Flow Analysis In Aneurysms by Proper Orthogonal Decomposition

Gary Han Chang

University of Massachusetts Amherst

Yahya Modarres-Sadeghi

University of Massachusetts Amherst, modarres@engin.umass.edu

Follow this and additional works at: http://escholarship.umassmed.edu/cts_retreat

 Part of the [Biomechanical Engineering Commons](#), [Biomechanics and Biotransport Commons](#), [Fluid Dynamics Commons](#), and the [Physiological Processes Commons](#)



This work is licensed under a [Creative Commons Attribution-Noncommercial-Share Alike 3.0 License](#).

Gary Han Chang and Yahya Modarres-Sadeghi, "A Reduced Order Model For Efficient Physiological Flow Analysis In Aneurysms by Proper Orthogonal Decomposition" (May 20, 2016). *UMass Center for Clinical and Translational Science Research Retreat*. Paper 4. http://escholarship.umassmed.edu/cts_retreat/2016/posters/4

This material is brought to you by eScholarship@UMMS. It has been accepted for inclusion in UMass Center for Clinical and Translational Science Research Retreat by an authorized administrator of eScholarship@UMMS. For more information, please contact Lisa.Palmer@umassmed.edu.

A Reduced Order Model For Efficient Physiological Flow Analysis In Aneurysms by Proper Orthogonal Decomposition

Gary Han Chang¹, Yahya Modarres-Sadeghi¹

¹Mechanical Engineering, University of Massachusetts, Amherst, Amherst, Massachusetts, USA

Abstract

Simulating physiological flows using computational fluid dynamics (CFD) remains to be computationally expensive and difficult for clinical usage because of the physiological flow and geometrical complexity involved in patient specific situations. We use the reduced order modeling (ROM) of such systems with high nonlinearity and geometrical non-uniformity to replace the full, nonlinear model with a low-degrees of freedom ROM model. We construct ROM models by the proper orthogonal decomposition (POD) method to estimate the flow-induced wall shear stress (WSS) and pressure loading of a simplified abdominal aortic aneurysm and a bifurcation cerebral aneurysm. This method allows us to investigate a wide range of different physiological flow parameters without conducting the computationally expensive CFD simulations repetitively, which is promising for clinical usage.

We obtain a set of snapshots from a set of flow simulations with multiple variable parameters, called the training set. The training set should be simulated in a parameter space that contains all the physiological parameters of interest. We show that both the velocity and pressure distributions are well reconstructed when compared with the exact values with a small number of modes. A mesh-less shell model is used to estimate the aneurysm sidewall's in-plane stresses. Sidewalls with non-uniform thickness are considered to study the influence of local weakness on the aneurysm's risk of failure. We found that the sensitivity of the material's strength to the local weakness depends on the aneurysms sidewall's Gaussian curvatures, the curvature to thickness ratio and the distribution of the flow loading. It is therefore critical to describe the distribution of curvature and thickness accurately when estimating the in-plane stress of aneurysms.

Yahya Modarres-Sadeghi
Associate Professor
Department of Mechanical and Industrial Engineering
University of Massachusetts, Amherst
413-545-2468
www.umass.edu/fsi